

Versatile hose reel that can be mounted on wall or ceiling.



Medium-sized reel in robust open design. Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling. Versatile and easily installed in industrial and workshop environments.

- Open design for easy cleaning and servicing
- · Unique stand design offers mounting flexibility

Product name	Hose Reel 893
Material recycling (% weight)	100
Connection hose length (m)	1
Colour	Black drum / Blue cover
Weight (kg)	14,5
Note	For suction hose
Corrosion resistance	Standard
Electric/Spring driven	Spring

(E



Type of hose ¹	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Max hose length	[model]
	Compressed air ,Water		10		12.5	1,5	10	30800793
	Compressed air ,Water		15		10	1,5	15	30800393
	Compressed air ,Water		15	12.5	10	1,5		30800693
	Water high pressure		15		10	25	15	30801793
	Water high pressure		15	10	10	25		30801893
			15	6	6	35		30802693
	Oil		10	12.5	12.5	7,5		30801693
	Compressed air ,Water		10	12.5	12.5	1,5		30800893
	Oil		10		12.5	7,5	10	30801593
			15		6	35	15	30802593
			10		12.5		10	30804993*
	Compressed air ,Water		10	12.5	12.5	2		30801093

^{*}For suction hose

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
В		-30 - 100				
G		-40 - 155				
J		-40 - 100				
I		-40 - 100				
E		-30 - 100				



[accessory]	[partno]
Roller guide.	30341550
Pivoting bracket.	30372407
Water gun in chromium plated brass	30400110
Water gun in stainless steel	30400210
Watergun EX	30400211
High temperature water gun	30400310
Air gun, standard.	30410110
Swivelling coupling 3/8(m)-3/8(m)HP	30431310
Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
Swivl. coupl.1/2(m)-3/8(f) brass	30431510
Swivl.coupl.1/2(m)-1/2(f) brass	30431610
Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
Swivl coupl. 1/2(m)-1/2(f) SS	30431910
Swivl.coupl.1/2(m)-3/4(f) SS	30432010



